

General Specifications

- Display 25mm LCD display, with white color LED backlight
- Capacities 30kg~600kg
- Keyboard 5 keys(Mechanical switch)
- Housing ABS plastic
- Max. Divisions 3,000d/6,000d
- ADC Sigma delta
- ADC update $\leq 1/10$ second
- Operate Temp $0^{\circ}\text{C} \sim +40^{\circ}\text{C}$
- Power AC adapter(12V/500mA), Internal rechargeable battery (lead acid 6V/1.2Ah)
- Packing Master carton 4 in 1, gross weight 9.5kg, dimension 0.105m^3 , 40 feet container can load 2000 machine, 20 feet container can load 1000 machine



- Easy to use - front panel configuration
- SGS 500% safety approval
- Application: 1. Reading lock 2. Weighing units conversion 3. Tare
- S hook(30kg), G hook(>30kg)
- Battery provide up to 40 hours of continuous use(without backlight)
- Optional remote controller (except 30kg)
- Optional rear display



DR Crane Scales

Model Number	Capacity	Readability	Division	Approx. weight	Approval
DR-30K	30kg	10g	3,000d	1.8kg	CE, GS
DR-60K	60kg	10g	6,000d	2kg	CE, GS
DR-150K	150kg	20g	7,500d	2kg	CE, GS
DR-300K	300kg	50g	6,000d	2kg	CE, GS
DR-600K	600kg	100g	6,000d	2kg	CE, GS

Options



Dimensions(mm)

