

T28 Weighing Scales

General Specifications

- Display 25mm digit LCD display, with white LED backlight
- Capacities 3kg~25kg
- Pan size 230x190mm
- Keyboard 3keys(Membrane keyboard)
- Housing ABS plastic
- Max. Divisions 3,000e; 2x3,000e; 15,000d
- ADC Sigma delta
- ADC update $\leq 1/10$ second
- Operate Temp $-10^{\circ}\text{C} \sim +40^{\circ}\text{C}$
- Power AC adapter (12V/500mA) or rechargeable battery (6V/4Ah)
- Gross weight 3.5kg
- Packing Master carton 4 in 1, dimension 0.101m^3 , 40 feet container can load 2100 machine, 20 feet container can load 1050 machine



- Waterproof housing designed, rugged and dependable
- Standard SST pan
- Battery provide up to 70 hours of continuous use (without backlight)
- Optional rear display
- Optional initial-verification



T28 Weighing Scales

Model Name	Capacity	Readability	Division	Approx. weight	Approval
T28-3K	3kg	0.2g	15,000d	3.5kg	CE
T28-6K	6kg	0.5g	15,000d	3.5kg	CE
T28-15K	15kg	1g	15,000d	3.5kg	CE
T28-25K	25kg	2g	15,000d	3.5kg	CE
T28-3K-M	3kg	1g	3,000e	3.5kg	CE, OIML
T28-6K-M	6kg	2g	3,000e	3.5kg	CE, OIML
T28-15K-M	15kg	5g	3,000e	3.5kg	CE, OIML
T28-25K-M	25kg	10g	3,000e	3.5kg	CE, OIML
T28-6K-MR	6kg	1g/2g	2x3,000e	3.5kg	CE, OIML
T28-15K-MR	15kg	2g/5g	2x3,000e	3.5kg	CE, OIML
T28-25K-MR	25kg	5g/10g	2x3,000e	3.5kg	CE, OIML

Options



Dimensions(mm)

